



General	
Marketing Area	Europe
Transponder	DVB-T2-FTA (Metal Housing)
Power Voltage	AC 100-200V ~ 50/60 Hz
Power Consumption	< 8W

System	
DDR II	1G bit
Flash Size	32 MB bit

Decode	
Video Decoder	MPEG-2 MP@HL, AVC/H.264 HP@L4., MPEG-4 ASP Supported
Audio Decoder	ACC/AC3/PCM
Video Output Ratio	4:3/16:9/Auto
Video Resoultion	1920 * 1080

Dimension	
Body Size	W188 x 120D x 38H mm
Packing Size	W214 x 185D x 64H mm

Terminal	
L/R Audio Output	Yes
CVBS Video Output	Yes

Accessories	
Remote control	Yes
AV cable	Optional
Full HD cable	Optional

Features	
OSD Language	Multi language
Optional	Media playback (MP3, FLAC, JPG, JPEG, MPG, MPEG, VOB, AVI, TS, TRP, M2T, M2TS, MP4, MKV, MOV, DIVX(Optional))
Record through USBHDD	Yes
7 days EPG (Electronic Program Guide)	Yes
DVB subtitle	Yes
Timeshift through USBHDD	Yes
Teletext	VBI/OSD
Easy first installation	Yes
Channel search with automatic manual	Yes
TV and radio list handling	Yes
Parents lock	Yes
Favorite list editing	Yes
Timer setting	Yes
OTA upgrade	Yes

Tuner & Channel	
RF input connector	IEC Female
RF output (Loophrough)	Yes
Receiving Channel Range	174~230Mhz, 470~862MHz
Modulation	QPSK/ 16QAM/ 64QAM/ 256QAM
FFT size	1K, 2K, 4K, 8K, 16K and 32K
Code rate	1/2, 2/3, 3/4, 5/6, 7/8
Guard interval	1/128, 1/32, 1/16, 19/256, 1/8, 19/128, 1/4
Band width	6/7/8 MHz